

Tenor[®] AX Series

- 8, 16, 24 or 48 Analog line and trunk interfaces
- Up to 48 simultaneous VoIP calls
- Available in MultiPath or Gateway configurations
- Integrated H.323 gatekeeper and SIP B2BUA for Survivability**
- Transparent MultiPath Call Routing
- Answer and Disconnect Supervision
- IVR/RADIUS AAA compliant (Multi-lingual IVR)
- SelectNet™ provides superior voice quality
- Support for external Quintum Call Routing Server*
- Support for external Quintum Tenor Monitor
- Support for external Remote Management Session Server*



A more intelligent way to implement VoIP

The Quintum® Tenor® AX Series gives businesses with analog voice infrastructures an easy, cost-effective way to capitalize on the power of Voice over IP (VoIP). The Tenor integrates a gateway, a gatekeeper, and intelligent call routing, and supports QoS all in one solution. With its MultiPath architecture, the Tenor connects to the data network through a 10/100 Ethernet interface, the voice network through either a PBX or phone, and the public switched telephone network.

Patented SelectNet™ Technology assures high quality voice

The Tenor employs its patented SelectNet™ Technology to monitor calls for jitter, packet loss and latency, and can transparently switch mid-call to the voice network whenever conditions demand.

More intelligence means greater flexibility

With its MultiPath Call Routing, the Tenor can intelligently route calls between the PBX, the PSTN, and the IP network, to achieve the best combination of cost and quality. The Tenor can also route calls over IP to reduce costs, and then transparently "hop off" to the PSTN, to reach off-net locations. No other VoIP solution can match this flexibility.

More intelligence means easier installation

With its MultiPath architecture, the Tenor is the only VoIP solution that can be installed without upgrades to the existing voice or data networks.

More intelligence means greater reliability

The Tenor is designed to pass calls through to the existing voice network in the event of system malfunction—even a total power failure.

More intelligence means less network congestion

With its PacketSaver™* Technology, the Tenor reduces bandwidth consumption up to 57%, by combining voice packets from several calls into a single packet to minimize packet overhead.

More intelligence means better management

The Tenor comes with a set of easy to use configuration and management tools, including Tenor Configuration Manager (GUI) and Wizard, and the Tenor Monitor that offers realtime monitoring of alarms, call status and CDRs. Tenors can easily be remotely managed behind NAT firewalls utilizing the Tenor Remote Management Session Server.*

Tenor AX MultiPath Switch

CALL MANAGEMENT FEATURES

- Automatic call type detection: Voice/Modem/Fax
- Answer and Disconnect Supervision
- Trunk group support
- Public and private dial plan support
- User programmable dial plan support
- Forced IP routing and IP port mapping
- Pass-through support for calls to Toll-Free, local and special service numbers (ie. emergency services, etc.)
- Automatic appending and stripping of digits to dialed numbers
- Call Detail Records
- Least cost routing with external Quintum VoIP Call Routing Server*
- Type I Caller ID/Name support (Telcordia, ETSI, NTT and DTMF)

TECHNICAL SPECIFICATIONS

Telephony Specifications

- Voice algorithms: G.723.1a, G.729ab, G.711
- Auto codec negotiation
- Fax support: Industry standard T.38 and Group III at 2.4, 4.8, 7.2, 9.6, 14.4 Kbps
- Modem over IP
- Choice of 8, 16, or 24 FXS and/or FXO configurations or a 48 FXO only configuration
- Standard 50 pin RJ-21 Telco connectors
- Coding: A-law, μ -law
- Enhanced (Carrier Grade) Echo Cancellation: ITU Rec. G168, up to 128 msec tailsize
- Loop Start, Reverse Battery, Battery Disconnect
- Tandem/TDM switching
- Maximum Call Rate: 1,800 calls/hour

IP Network Specifications

- LAN Interface: 1 Fast Ethernet port (10/100 Base-T)
- Standard RJ-45 Interface (IEEE 802.3) for 10 Base-T or 100 Base-T connections
- DHCP Client
- QoS Support: IP TOS, DiffServ

VoIP Network Specifications

- H.323 v.3 Gateway and Integrated Gatekeeper
- SIP User Agent
- SIP Back-to-back User Agent (B2BUA)**
- SIP RFC2833 In-band DTMF signaling
- SIP Supplementary Services
- SIP Refer Method Support
- Message Waiting
- IVR/RADIUS server support for AAA with integrated multi-lingual IVR
- Adaptive Voice Activity Detection (VAD) with Comfort Noise Generation (CNG)
- Adaptive Jitter Buffer
- Packet Loss Compensation
- NATAccess™
- Security: IP Filtering
- Up to 48 simultaneous VoIP calls
- Support for DNS Addressing

Configuration / Management

- Quintum Tenor Configuration Manager (GUI) for configuration of remote individual Tenors.
- Quintum Tenor Monitor (GUI) for alarm monitoring, call monitoring and CDR monitoring
- SNMPv2 Agent
- Command Line Interface

GENERAL SPECIFICATIONS

Dimensions: 1U High Chassis

- W 17 3/8" x H 1 3/4" x D 10 3/4"
- W 44.5cm x H 4.5cm x D 27.6cm
- Maximum weight: 10 lbs. (4.55kg)
- AC Power: 100-240 Volts AC, 50/60 Hz, 60 watts
- Operating temperature: 40° - 104° F (5° - 40° C)
- Operating humidity: 20% - 80% non-condensing
- Telco: FCC Part 68, TS-016, TBR4, TS-038, CS03
- EMC: FCC Part 15 EN55022, EN55024, EN61000-2-3, EN61000-3-3, AS/NZS3260
- Safety: UL60950, EN60950, AS/NZS60950

Tenor AX Series	MultiPath AXM Series	Station AXG Series	Trunk AXT Series	Enterprise AXE Series
8 Simultaneous VoIP Calls	8 FXS / 8 FXO	8 FXS / 0 FXO	0 FXS / 8 FXO	8 FXS / 2 FXO
16 Simultaneous VoIP Calls	16 FXS / 16 FXO	16 FXS / 0 FXO	0 FXS / 16 FXO	16 FXS / 2 FXO
24 Simultaneous VoIP Calls	24 FXS / 24 FXO	24 FXS / 0 FXO	0 FXS / 24 FXO	24 FXS / 2 FXO
48 Simultaneous VoIP Calls			0 FXS / 48 FXO	



* Quintum product purchased separately
** Not supported in initial software release

